

Strip
Series


24V Operation Light Strip



CRI (Min.) : 65

Beam Angle : 120°

Operating Temp. : -30°C ~ +60°C

Connector : 3.5mm pitch, 2-pin,
AC/DC 1400V, 1A

Performance Information

Part Number	CCT (K, Typ.)	Luminous Flux (lm, Typ.)	Power (W, Typ.)	Op. Current (mA, Typ.)	Op. Voltage (V, Typ.)	PCB Dimension (mm)
LLMLMR010ANWWWV01	2875~3200	80	1.44	60	24	100×14×1.6t
LLMLMR010ANWWW01	3800~4600	100	1.44	60	24	100×14×1.6t
LLMLMR015ANCWL01	6000~8200	160	2.88	120	24	150×14×1.6t
LLMLMR020ANWWW01	3800~4600	200	2.88	120	24	200×14×1.6t
LLMLMR030ANWWWV01	2875~3200	235	4.32	180	24	300×14×1.6t
LLMLMR030ANWWL03	3200~3800	255	4.32	180	24	300×14×1.6t
LLMLMR030ANWWL04	3800~4600	300	4.32	180	24	300×14×1.6t
LLMLMR030ANWWW02 (Free Polar Available)	3800~4600	300	4.32	180	24	300×14×1.6t
LLMLMR030ANWWL05	4600~6000	315	4.32	180	24	300×14×1.6t
LLMLMR030ANCWL03	6000~8200	320	4.32	180	24	300×14×1.6t
LLMLMR030ANWWL01	3200~3800	255	4.32	180	24	300×25×1.6t
LLMLMR030ANWWL02	6000~6700	320	4.32	180	24	300×25×1.6t