

# SAFETY DATA SHEET



according to Commission Regulation (EU) 2020/878 as amended

## Lakier PVB 60

Creation date	17th October 2022	Version	10.0
Revision date	06th January 2023		

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier**  
Substance / mixture: Lakier PVB 60 mixture  
UFI: RH20-M0YR-U00E-0J55
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**  
**Mixture's intended use**  
Varnish for protecting PCBs  
**Main intended use**  
PC-PNT-3 Paints/coatings - Protective and functional  
**Mixture uses advised against**  
The product should not be used in ways other than those referred in Section 1.
- 1.3. Details of the supplier of the safety data sheet**  
**Manufacturer**  
Name or trade name: AG TermoPasty Grzegorz Gąsowski  
Address: Kolejowa 33 E, Sokoły, 18-218 Poland  
Identification number (CRN): 200133730  
VAT Reg No: PL9661767714  
Phone: 862741342  
E-mail: biuro@termopasty.pl  
Web address: www.termopasty.pl  
**Competent person responsible for the safety data sheet**  
Name: AG TermoPasty Grzegorz Gąsowski  
E-mail: biuro@termopasty.pl
- 1.4. Emergency telephone number**  
European emergency number: 112

### SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture**  
**Classification of the mixture in accordance with Regulation (EC) No 1272/2008**  
The mixture is classified as dangerous.
- Flam. Liq. 2, H225  
Skin Irrit. 2, H315  
Eye Dam. 1, H318  
STOT SE 3, H336
- Full text of all classifications and hazard statements is given in the section 16.
- Most serious adverse physico-chemical effects**  
Highly flammable liquid and vapour.
- Most serious adverse effects on human health and the environment**  
May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye damage.

### 2.2. Label elements

#### Hazard pictogram



#### Signal word

Danger

# SAFETY DATA SHEET



according to Commission Regulation (EU) 2020/878 as amended

## Lakier PVB 60

Creation date 17th October 2022  
Revision date 06th January 2023 Version 10.0

### Hazardous substances

acetone  
butan-1-ol

### Hazard statements

H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H336 May cause drowsiness or dizziness.

### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing mist/vapours/spray.  
P264 Wash hands and exposed parts of the body thoroughly after handling.  
P280 Wear eye protection.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a doctor.  
P312 Call a POISON CENTER if you feel unwell.

### 2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Mixture of substances and additives specified below.

**Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment**

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 606-001-00-8 CAS: 67-64-1 EC: 200-662-2 Registration number: 01-2119471330-49-XXXX	acetone	50-75	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	1
Index: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7 Registration number: 01-2119457558-25-XXXX	isopropanol	≤20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	1
Index: 603-004-00-6 CAS: 71-36-3 EC: 200-751-6 Registration number: 01-2119484630-38-XXXX	butan-1-ol		Flam. Liq. 3, H226 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335, H336	1

#### Notes

1 A substance for which exposure limits are set.

Full text of all classifications and hazard statements is given in the section 16.

# SAFETY DATA SHEET



according to Commission Regulation (EU) 2020/878 as amended

## Lakier PVB 60

Creation date	17th October 2022	Version	10.0
Revision date	06th January 2023		

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

##### If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

##### If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water/shower.

##### If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. No neutralization should be performed in any case! Rinsing should be continued for 10-30 minutes from the inner to the outer eye corner to make sure that the other eye is not involved. Depending on the situation, call medical rescue service or ensure medical treatment as promptly as possible. Everyone must be referred for treatment even if affected only a little.

##### If swallowed

DO NOT INDUCE VOMITING! Rinse out the mouth with water and provide 2-5 dL of water. Provide medical treatment if the person has any health problems.

#### 4.2. Most important symptoms and effects, both acute and delayed

##### If inhaled

Inhaling vapours can cause corrosion of the breathing system. May cause drowsiness or dizziness.

##### If on skin

Causes skin irritation.

##### If in eyes

Causes serious eye damage.

##### If swallowed

Corrosion of the digestion system can occur.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

##### Unsuitable extinguishing media

Water - full jet.

#### 5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

#### 5.3. Advice for firefighters

Use a self-contained breathing apparatus and full-body protective clothing. Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Highly flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale aerosols. Prevent contact with skin and eyes.

# SAFETY DATA SHEET



according to Commission Regulation (EU) 2020/878 as amended

## Lakier PVB 60

Creation date 17th October 2022  
Revision date 06th January 2023 Version 10.0

### 6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

### 6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

### 6.4. Reference to other sections

See the Section 7, 8 and 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale aerosols. Prevent contact with skin and eyes. No smoking. Use only non-sparking tools. Wash hands and exposed parts of the body thoroughly after handling. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Store locked up. Keep container tightly closed. Keep cool.

Content	Packaging type	Material of package
1 l	jerry can	FE
50 ml	bottle	HDPE

### The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

### 7.3. Specific end use(s)

not available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

#### European Union

#### Commission Directive 2000/39/EC

Substance name (component)	Type	Value	Note
acetone (CAS: 67-64-1)	OEL 8 hours	1210 mg/m <sup>3</sup>	
	OEL 8 hours	500 ppm	

#### United Kingdom

#### EH40/2005 Workplace exposure limits (Fourth Edition 2020)

Substance name (component)	Type	Value	Note
acetone (CAS: 67-64-1)	WEL 8h	1210 mg/m <sup>3</sup>	
	WEL 8h	500 ppm	
	WEL 15min	3620 mg/m <sup>3</sup>	
	WEL 15min	1500 ppm	
isopropanol (CAS: 67-63-0)	WEL 8h	999 mg/m <sup>3</sup>	
	WEL 8h	400 ppm	
	WEL 15min	1250 mg/m <sup>3</sup>	
	WEL 15min	500 ppm	

# SAFETY DATA SHEET



according to Commission Regulation (EU) 2020/878 as amended

## Lakier PVB 60

Creation date	17th October 2022	Version	10.0
Revision date	06th January 2023		

### United Kingdom

### EH40/2005 Workplace exposure limits (Fourth Edition 2020)

Substance name (component)	Type	Value	Note
butan-1-ol (CAS: 71-36-3)	WEL 15min	154 mg/m <sup>3</sup>	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.
	WEL 15min	50 ppm	

### DNEL

#### acetone

Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Inhalation	2420 mg/m <sup>3</sup>	Acute effects local		
Workers	Dermal	186 mg/kg bw/day	Chronic effects systemic		
Workers	Inhalation	1210 mg/m <sup>3</sup>	Chronic effects systemic		
Consumers	Dermal	62 mg/kg bw/day	Chronic effects systemic		
Consumers	Inhalation	200 mg/m <sup>3</sup>	Chronic effects systemic		
Consumers	Oral	62 mg/kg bw/day	Chronic effects systemic		

#### butan-1-ol

Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Inhalation	10 mg/m <sup>3</sup>	Chronic effects systemic		
Consumers	Inhalation	55 mg/m <sup>3</sup>	Chronic effects systemic		
Consumers	Oral	3.125 mg/kg	Chronic effects systemic		

#### isopropanol

Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Inhalation	500 mg/m <sup>3</sup>	Chronic effects systemic		
Workers	Dermal	888 mg/kg bw/day	Chronic effects systemic		
Consumers	Inhalation	89 mg/m <sup>3</sup>	Chronic effects systemic		
Consumers	Dermal	319 mg/kg bw/day	Chronic effects systemic		
Consumers	Oral	26 mg/kg bw/day	Chronic effects systemic		

### PNEC

#### acetone

Route of exposure	Value	Value determination	Source
Drinking water	10.6 mg/l		
Marine water	1.06 mg/l		
Sea sediments	30.4 mg/kg of food		
Freshwater sediment	30.4 mg/kg of food		

# SAFETY DATA SHEET



according to Commission Regulation (EU) 2020/878 as amended

## Lakier PVB 60

Creation date 17th October 2022  
Revision date 06th January 2023 Version 10.0

acetone

Route of exposure	Value	Value determination	Source
Soil (agricultural)	29.5 mg/kg of dry substance of soil		
Microorganisms in sewage treatment	100 mg/l		

butan-1-ol

Route of exposure	Value	Value determination	Source
Drinking water	0.082 mg/l		
Marine water	0.0082 mg/l		
Water (intermittent release)	2.25 mg/l		
Freshwater sediment	0.178 mg/kg		
Sea sediments	0.0178 mg/kg		
Soil (agricultural)	0.015 mg/kg of dry substance of soil		

isopropanol

Route of exposure	Value	Value determination	Source
Drinking water	140.9 mg/l		
Marine water	140.9 mg/l		
Freshwater sediment	552 mg/kg of dry substance		
Freshwater environment	552 mg/kg of dry substance		
Soil (agricultural)	28 mg/kg of dry substance		

### 8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

#### Eye/face protection

Protective goggles or face shield (based on the nature of the work performed).

#### Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

#### Respiratory protection

Halfmask with a filter against organic vapours or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment.

#### Thermal hazard

Data not available.

#### Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	characteristic
Melting point/freezing point	data not available
Boiling point or initial boiling point and boiling range	>35 °C
Flammability	Highly flammable liquid and vapour.

# SAFETY DATA SHEET



according to Commission Regulation (EU) 2020/878 as amended

## Lakier PVB 60

Creation date 17th October 2022  
Revision date 06th January 2023 Version 10.0

Lower and upper explosion limit	data not available
Flash point	data not available
Auto-ignition temperature	data not available
Decomposition temperature	data not available
pH	non-soluble (in water)
Kinematic viscosity	data not available
Solubility in water	data not available
Solubility in fats	data not available
Partition coefficient n-octanol/water (log value)	data not available
Vapour pressure	data not available
Density and/or relative density	
Density	0,792 g/cm <sup>3</sup>
Relative vapour density	data not available
Particle characteristics	data not available
Form	liquid
<b>9.2. Other information</b>	
Evaporation rate	data not available
Ignition temperature	38 °C

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

not available

#### 10.2. Chemical stability

The product is stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Unknown.

#### 10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

#### 10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

#### 10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

No toxicological data is available for the mixture.

##### Acute toxicity

Based on available data the classification criteria are not met.

acetone

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD <sub>50</sub>	5800 mg/kg		Rat (Rattus norvegicus)	
Inhalation (vapor)	LC <sub>50</sub>	76000 mg/m <sup>3</sup>	4 hours	Rat (Rattus norvegicus)	
Dermal	LD <sub>50</sub>	7400 mg/kg		Rabbit	
Dermal	LD <sub>50</sub>	7400 mg/kg		Guinea-pig (Cavia aperea f. porcellus)	

# SAFETY DATA SHEET



according to Commission Regulation (EU) 2020/878 as amended

## Lakier PVB 60

Creation date	17th October 2022	Version	10.0
Revision date	06th January 2023		

butan-1-ol

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD <sub>50</sub>	2292 mg/kg		Rat (Rattus norvegicus)	
Dermal	LD <sub>50</sub>	3430 mg/kg		Rabbit	
Inhalation	LC <sub>50</sub>	17.76 mg/l	4 hours	Rat (Rattus norvegicus)	

isopropanol

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Inhalation	LC <sub>50</sub>	>5 mg/l	4 hours	Rat	
Oral	LD <sub>50</sub>	>2000 mg/kg		Rat	
Skin	LD <sub>50</sub>	>2000 mg/kg		Rabbit	

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/irritation**

Causes serious eye damage.

acetone

Route of exposure	Result	Method	Exposure time	Species
Eye		OECD 405		

**Respiratory or skin sensitisation**

Based on available data the classification criteria are not met.

**Germ cell mutagenicity**

Based on available data the classification criteria are not met.

**Carcinogenicity**

Based on available data the classification criteria are not met.

**Reproductive toxicity**

Based on available data the classification criteria are not met.

**Toxicity for specific target organ - single exposure**

May cause drowsiness or dizziness.

**Toxicity for specific target organ - repeated exposure**

Based on available data the classification criteria are not met.

**Aspiration hazard**

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. Based on available data the classification criteria are not met.

**11.2. Information on other hazards**

not available

**SECTION 12: Ecological information**

**12.1. Toxicity**

**Acute toxicity**

acetone

Parameter	Value	Exposure time	Species	Environment
LC <sub>50</sub>	8800 mg/l	48 hours	Invertebrates	Fresh water
LC <sub>50</sub>	2100 mg/l	24 hours	Invertebrates	Salt water
LOEC	530 mg/l	8 days	Algae and other aquatic plants	Fresh water
NOEC	430 mg/l	96 hours	Algae and other aquatic plants	Salt water
LC <sub>50</sub>	5540 mg/l	96 hours	Fish (Oncorhynchus mykiss)	Fresh water



# SAFETY DATA SHEET



according to Commission Regulation (EU) 2020/878 as amended

## Lakier PVB 60

Creation date 17th October 2022  
Revision date 06th January 2023 Version 10.0

acetone

Parameter	Value	Exposure time	Species	Environment
LC <sub>50</sub>	11000 mg/l	96 hours	Fish	Salt water

butan-1-ol

Parameter	Value	Exposure time	Species	Environment
LC <sub>50</sub>	1376 mg/l	96 hours	Fish (Pimephales promelas)	
EC <sub>50</sub>	1328 mg/l	48 hours	Daphnia (Daphnia magna)	
EC <sub>50</sub>	4390 mg/l	17 hours	Microorganisms (Pseudomonas putida)	
EC <sub>50</sub>	225 mg/l	96 hours	Algae and other aquatic plants (Pseudokirchneriella subcapitata)	
NOEC	4.1 mg/l	21 days	Daphnia (Daphnia magna)	
EC <sub>50</sub>	18 mg/l	21 days	Daphnia (Daphnia magna)	

isopropanol

Parameter	Value	Exposure time	Species	Environment
LC <sub>50</sub>	>100 mg/l	48 hours	Fish (Leuciscus idus)	
EC <sub>50</sub>	>100 mg/l	48 hours	Daphnia (Daphnia magna)	
EC <sub>50</sub>	>100 mg/l	72 hours	Algae (Scenedesmus subspicatus)	

### Chronic toxicity

acetone

Parameter	Value	Exposure time	Species	Environment
NOEC	2212 mg/l	24 hours	Invertebrates (Daphnia magna)	

### 12.2. Persistence and degradability

Data not available.

### 12.3. Bioaccumulative potential

Data not available.

### 12.4. Mobility in soil

Data not available.

### 12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

### 12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

### 12.7. Other adverse effects

Data not available.

## SECTION 13: Disposal considerations

# SAFETY DATA SHEET



according to Commission Regulation (EU) 2020/878 as amended

## Lakier PVB 60

Creation date	17th October 2022	Version	10.0
Revision date	06th January 2023		

### 13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

#### Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

#### Packaging waste type code

15 01 02 plastic packaging  
15 01 10 packaging containing residues of or contaminated by hazardous substances \*  
(\* ) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

## SECTION 14: Transport information

### 14.1. UN number or ID number

UN 1993

### 14.2. UN proper shipping name

FLAMMABLE LIQUID, N.O.S. (Acetone)

### 14.3. Transport hazard class(es)

3 Flammable liquids

### 14.4. Packing group

III - substances presenting low danger

### 14.5. Environmental hazards

not relevant

### 14.6. Special precautions for user

Reference in the Sections 4 to 8.

### 14.7. Maritime transport in bulk according to IMO instruments

not relevant

#### Additional information

Hazard identification No.

30

UN number

1993

Classification code

F1

Safety signs

3



# SAFETY DATA SHEET



according to Commission Regulation (EU) 2020/878 as amended

## Lakier PVB 60

Creation date	17th October 2022	Version	10.0
Revision date	06th January 2023		

### Road transport - ADR

Special provisions	274, 601
Limited quantities	5 L
Excepted quantities	E1

### Packaging

Packing instructions	P001, IBC03, LP01, R001
Mixed packing provisions	MP19

### Portable tanks and bulk containers

Guidelines	T4
Special provisions	TP1, TP29

### ADR tank

Tank code	LGBF
Vehicles for tank carriage	FL
Transport category	3
Tunnel restriction code	(D/E)

### Special provision for

packages	V12
operation	S2

### Railway transport - RID

Special provisions	274, 601
Excepted quantities	E1

### Packaging

Packing instructions	P001, IBC03, LP01, R001
Mixed packing provisions	MP19

### Portable tanks and bulk containers

Guidelines	T4
Special provisions	TP1, TP29

### RID Tanks

Tank code	LGBF
Transport category	0

### Special provision for

packages	W 12
----------	------

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Product contains reportable explosives precursors: Reporting of suspicious transactions, disappearances and thefts according to Regulation (EU) 2019/1148, Article 9.

### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out (mixture).

## SECTION 16: Other information

### A list of standard risk phrases used in the safety data sheet

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

# SAFETY DATA SHEET



according to Commission Regulation (EU) 2020/878 as amended

## Lakier PVB 60

Creation date	17th October 2022	Version	10.0
Revision date	06th January 2023		

### Guidelines for safe handling used in the safety data sheet

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing mist/vapours/spray.
- P264 Wash hands and exposed parts of the body thoroughly after handling.
- P280 Wear eye protection.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a doctor.
- P312 Call a POISON CENTER if you feel unwell.

### A list of additional standard phrases used in the safety data sheet

- EUH066 Repeated exposure may cause skin dryness or cracking.

### Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

### Key to abbreviations and acronyms used in the safety data sheet

- ADR European agreement concerning the international carriage of dangerous goods by road
- BCF Bioconcentration Factor
- CAS Chemical Abstracts Service
- CLP Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
- EC Identification code for each substance listed in EINECS
- EC<sub>50</sub> Concentration of a substance when it is affected 50% of the population
- EINECS European Inventory of Existing Commercial Chemical Substances
- EmS Emergency plan
- EU European Union
- EuPCS European Product Categorisation System
- IATA International Air Transport Association
- IBC International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
- ICAO International Civil Aviation Organization
- IMDG International Maritime Dangerous Goods
- IMO International Maritime Organization
- INCI International Nomenclature of Cosmetic Ingredients
- ISO International Organization for Standardization
- IUPAC International Union of Pure and Applied Chemistry
- LC<sub>50</sub> Lethal concentration of a substance in which it can be expected death of 50% of the population
- LD<sub>50</sub> Lethal dose of a substance in which it can be expected death of 50% of the population
- log Kow Octanol-water partition coefficient
- NOEC No observed effect concentration
- OEL Occupational Exposure Limits
- PBT Persistent, Bioaccumulative and Toxic
- ppm Parts per million
- REACH Registration, Evaluation, Authorisation and Restriction of Chemicals
- RID Agreement on the transport of dangerous goods by rail
- UN Four-figure identification number of the substance or article taken from the UN Model Regulations
- UVCB Substances of unknown or variable composition, complex reaction products or biological materials
- VOC Volatile organic compounds
- vPvB Very Persistent and very Bioaccumulative
- Acute Tox. Acute toxicity
- Eye Dam. Serious eye damage

# SAFETY DATA SHEET



according to Commission Regulation (EU) 2020/878 as amended

## Lakier PVB 60

Creation date	17th October 2022	Version	10.0
Revision date	06th January 2023		

Flam. Liq.	Flammable liquid
Skin Irrit.	Skin irritation
STOT SE	Specific target organ toxicity - single exposure

### Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

### Recommended restrictions of use

not available

### Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.  
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

### The changes (which information has been added, deleted or modified)

The version 10.0 replaces the SDS version from 26 January 2023. Changes were made in sections 1, 2, 13, 15 and 16.

### Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.